

UNCLASSIFIED



**DoD ANNEX
FOR
MOBILE DEVICE FUNDAMENTALS (MDF)
PROTECTION PROFILE (PP) V3.2**

Version 1, Release 3

01 February 2022

Developed by DISA for the DoD

UNCLASSIFIED

Trademark Information

Names, products, and services referenced within this document may be the trade names, trademarks, or service marks of their respective owners. References to commercial vendors and their products or services are provided strictly as a convenience to our users, and do not constitute or imply endorsement by DISA of any non-Federal entity, event, product, service, or enterprise.

REVISION HISTORY

Version	Date	Description
V1R3	01 February 2022	- Updated Table 4-1, Function 1: Changed password complexity rule from no more than two to no more than four repeating or sequential characters.
V1R2	26 November 2021	- Added Application Note to Function 37 in Table 3-2 - Updated Function 37 in Table 4-1 (removed the following Table 2 auditable events: FIA_AFL_EXT.1, Excess of authentication failure limits and FMT_SMF_EXT.2, Initiation of unenrollment)
V1R1	01 May 2021	Initial Release

TABLE OF CONTENTS

	Page
1. INTRODUCTION.....	1
1.1 Background	1
1.2 Scope	1
1.3 Relationship to Security Technical Implementation Guides (STIGs).....	1
1.4 Document Revisions	2
2. CONVENTIONS.....	3
3. DOD-MANDATED SECURITY TARGET CONTENT.....	4
3.1 DoD-Mandated Selections and Assignments.....	4
3.2 DoD-Mandated Selection-Based, Optional, and Objective Functions.....	8
4. OTHER DOD MANDATES	10
4.1 Federal Information Processing Standard (FIPS) 140-2	10
4.2 Federal Information Processing Standard (FIPS) 201-2	10
4.3 Core and Carrier-Installed Applications on Mobile Devices	10
4.4 DoD-Mandated Configuration	10

LIST OF TABLES

	Page
Table 3-1: PP SFR Selections	4
Table 3-2: Management Functions (Table 7 of MDF PP)	5
Table 3-3: Management Functions (From PP-Module for Bluetooth)	8
Table 3-4: Management Functions (From MDFPP Extended Package for WLAN Clients)	8
Table 4-1: Configuration Values	10

1. INTRODUCTION

1.1 Background

This Annex to the Protection Profile (PP) for the Mobile Device Fundamentals (Version 3.2, dated 15 April 2021) delineates PP content that must be included in the Security Target (ST) for the Target of Evaluation (TOE) to be fully compliant with DoD cybersecurity policies pertaining to information systems. This content includes DoD-mandated PP selections and assignments and PP Security Functional Requirements (SFRs) listed as optional or objective in the PP but that are mandated in DoD.

This Annex assumes the mobile device has also been validated against the PP-Module for Bluetooth, Extended Package for WLAN Client, and Functional Package for TLS. DoD selections and/or assignments for these packages/modules are included in this Annex. If the TOE includes an MDM agent, requirements in the DoD Annex for PP-Module for MDM Agents should also be included in the ST.

Deficiencies of the TOE with respect to the DoD Annex will be reported as appropriate under the Risk Management Framework for DoD Information Technology (DoD Instruction 8510.01). DoD may determine that a TOE that does not conform to this Annex may pose an unacceptable risk to DoD. Accordingly, any vendor seeking authorization for use of its product within DoD should include the additional PP specificity described in this Annex in its ST.

The MDF PP, in conjunction with this Annex, addresses the DoD-required cybersecurity controls in National Institute of Standards and Technology (NIST) Special Publication (SP) 800-53. Taken together, they supersede the DoD Mobile Operating System Security Requirements Guide.

1.2 Scope

The additional information in this document is applicable to all DoD-administered systems and all systems connected to DoD networks.

1.3 Relationship to Security Technical Implementation Guides (STIGs)

A successful Common Criteria evaluation certifies the capabilities of the TOE but does not ensure its subsequent secure operation. To address security concerns with the ongoing operation of the TOE in the field, a product-specific STIG is prepared in conjunction with the Common Criteria evaluation. The STIG lists the configuration requirements for DoD implementations of the TOE and is published in Extensible Configuration Checklist Description Format (XCCDF) to facilitate automation where feasible.

This Annex contains the required DoD configuration of features implementing the security management (FMT) class of SFRs listed in the MDF PP. For each applicable FMT SFR, the STIG will discuss the vulnerability associated with non-compliance configuration and provide step-by-step, product-specific procedures for checking for compliant configurations and fixing non-compliant configurations.

In most cases, the ST will not cover all security-relevant configurable parameters available in the TOE. However, the STIG will include these whenever they impact the security posture of DoD information systems and networks¹. Accordingly, the DoD Annex only addresses a subset of the controls expected to be included in a STIG.

1.4 Document Revisions

Comments or proposed revisions to this document should be sent via email to:
disa.stig_spt@mail.mil.

¹ For example, if the mobile operating system provides an exception to the data sharing restrictions found in FDP_ACF_EXT.1.2, a configuration setting should be included in the STIG to disable this feature.

2. CONVENTIONS

The following conventions are used to describe DoD-mandated ST content:

- If a PP SFR is not listed, there is no DoD-mandated selection or assignment for that SFR.
- For SFRs included in this annex:
 - *Italicized* text indicates a required selection. The presence of the selection indicates this is a DoD-mandated selection.
 - If a selection is not listed, its inclusion or exclusion does not impact DoD compliance.
 - Underlined text indicates additional text provided as a refinement.
 - ***Italicized and bold*** text indicates a required assignment within a selection.
 - ~~*Strikethrough and italicized*~~ text indicates the ST author must exclude the selection.

The Annex provides the minimum text necessary to disambiguate selections and assignments. Readers will have to view both the MDF PP and the DoD Annex simultaneously to place the Annex information in context.

3. DOD-MANDATED SECURITY TARGET CONTENT

3.1 DoD-Mandated Selections and Assignments

DoD mandates the following PP SFR selections and assignments for SFRs in Section 5 of the MDF PP:

Table 3-1: PP SFR Selections

SFR	Selections, Assignments, and Application Notes
FAU_GEN.1.1	<p>6. Specifically defined auditable event in Table 1:</p> <ul style="list-style-type: none"> FPT_TST_EXT.2/PREKERNAL, <i>Detected integrity violation</i> <p>Application note: Requirement applies only to integrity violation detections that can be logged by the audit logging component.</p> <p>7. Specifically defined auditable event in Table 2,</p> <ul style="list-style-type: none"> FIA_AFL_EXT.1 FIA_UAU.6 FMT_SMF_EXT.2, <i>Initiation of unenrollment</i> FPT_TUD_EXT.2 FPT_TUD_EXT.3
FCS_STG_EXT.1.4	the user
FDP_ACF_EXT.1.2	<p>the user</p> <p>Application note: The TSF is required to support the following two application process groups: Work Profile (Enterprise/Managed) and Personal Profile (BYOD/Unmanaged). In the majority of DoD use cases, the MD will be DoD owned and both application process groups will be enabled.</p>
FIA_UAU.5.1	<p><i>biometric fingerprint, iris, face, voice, hybrid (if supported by the TSF)</i></p> <p>Application note: Every biometric authentication function supported by the MD must be included in the ST.</p>
FIA_UAU_EXT.2.1	<p>list of actions = any action that enables access to the user's contact, calendar, messaging databases or other DoD sensitive information.</p> <p>Application note: Examples of actions that enable access to DoD sensitive information include but are not limited to voice dialing of stored contacts and voice-enabled personal assistant applications that allow queries for locally stored information.</p>
FIA_X509_EXT.2.1	<p><i>code signing for system software updates, code signing for mobile applications, code signing for integrity verification</i></p> <p>Application note: If management function is not supported by an operating system, appropriate mitigations should be provided.</p>
FIA_X509_EXT.2.2	<i>allow the user to choose whether to accept the certificate in these cases, accept the certificate</i>
FMT_MOF_EXT.1.2	See Table 3-2
FMT_SMF_EXT.1.1	See Table 3-2
FMT_SMF_EXT.2.1	<p>Include one of the following selections:</p> <p><i>-wipe of protected data</i></p>

SFR	Selections, Assignments, and Application Notes
	<p><u>-wipe of sensitive data (provided that the ST author has identified sensitive data in a manner to include all Enterprise applications and resident Enterprise application data, all data associated with Enterprise email, calendar and contact information, and all other local data storage accessible to Enterprise applications and email, calendar, and contact applications.</u></p> <p>Include one of the following selections:</p> <p><u>-remove Enterprise applications</u></p> <p><u>-remove all non-core applications (any non-factory-installed application)</u> (this is an assignment to other available remediation actions)</p>

Table 3-2: Management Functions (Table 7 of MDF PP)

Management Function	FMT_SMF_EXT.1.1 (Implemented)	FMT_MOF_EXT.1.1 (User Only)	Administrator	FMT_MOF_EXT.1.2 (Admin Only)
<div> Status Markers: M – Mandatory O – Optional/Objective Red highlighted text – Deviations from Table 6 in the MDF PP </div>				
3. Enable/disable VPN protection	M	O	M	-
4. List of all radios: cellular, Wi-Fi, Bluetooth, NFC (if the radio is supported by the MD, it must be included by the ST author)	M	O	M	-
5. assignment: microphone, camera (if supported by the MD)	M	-	M	O
8. a. Restricting the sources of applications, b. Specifying a set of allowed applications based on [assignment: application characteristics] (an application whitelist) (See application note below)	M	-	M	M
18. (See application note below)	M	-	M	M
19. Enable data at rest protection	M	-	M	M
20. Enable removable media's data at rest protection	M	-	M	M
21. Enable/disable location services	M	-	M	M
22. <u>Biometric Fingerprint, iris, face, voice, Hybrid Authentication Factor (if supported by the TSF)</u>	M	-	M	M
24. Enable/disable all data signaling over [assignment: list of externally accessible hardware ports]	M	-	M	M
25. (See application note below)	M	-	M	M
26. Enable/disable developer modes	M	-	M	M
27. Enable/disable bypass of local user authentication	M	-	M	M
28. Wipe Enterprise data	M	-	M	-

Management Function	FMT_SMF_EXT.1.1 (Implemented)	FMT_MOF_EXT.1.1 (User Only)	Administrator	FMT_MOF_EXT.1.2 (Admin Only)
<div> Status Markers: M – Mandatory O – Optional/Objective Red highlighted text – Deviations from Table 6 in the MDF PP </div>				
32. read audit logs kept by the TSF (See application note below)	M	-	M	-
33. configure [selection: <i>certificate, public-key</i>] used to validate digital signature on applications	M	-	M	M
36. configure the unlock banner	M	-	O	O
37. configure the auditable items	M	-	M	M
39. <i>USB mass storage mode</i>	M	-	M	M
40. enable/disable backup of <i>all applications</i> to <i>locally connected system, remote system</i>	M	-	M	M
41. a. <i>Hotspot functionality authenticated by [selection: pre-shared key, passcode, no authentication]</i> , b. <i>USB tethering authenticated by [selection: pre-shared key, passcode, no authentication]</i> (See application note below)	M	-	M	M
42. (See application note below)	M	-	M	M
43. place applications into application groups based on [assignment: <i>enterprise configuration settings</i>]	M	-	M	M
44. (See application note below)	M	-	M	O
46. Revoke Biometric template (<i>if biometric authentication is supported by the MD</i>)	M	-	M	O
47. [assignment: a. <i>enable/disable multi-user modes (if feature supported by MD)</i> b. <i>enable/disable automatic updates of system software (see function 15)</i> c. <i>wipe non-enterprise data</i> d. <i>enable/disable use of removable media</i>	M M M M	- - - -	M M M M	M M O M
Application Notes: 8. The application whitelist, in addition to controlling the installation of applications on the MD, must control user access/execution of all core and preinstalled applications or the MD must provide an alternate method of restricting user access/execution to core and pre-installed applications. Core application – any application integrated into the operating system (OS) by the OS or mobile device (MD) vendor. Pre-installed application – additional non-core applications included in the OS build by the OS vendor, MD vendor, or wireless carrier. 18. The ST author must select “ <i>f. all notifications</i> ” if there is no other means to administratively restrict applications from issuing notifications in the locked state where those notifications could include DoD sensitive information. If it is possible to administratively restrict notifications on a per-app basis, then it is permissible to allow notifications from applications that do not handle DoD sensitive information. In this case, the ST author must select: a. email notifications, b. calendar appointments, c. contact associated with phone call notification, d. text message notification.				

<p style="text-align: center;">Management Function</p> <div style="border: 1px solid black; padding: 5px; margin: 10px auto; width: fit-content;"> <p>Status Markers: M – Mandatory O – Optional/Objective Red highlighted text – Deviations from Table 6 in the MDF PP</p> </div>	FMT_SMF_EXT.1.1 (Implemented)	FMT_MOF_EXT.1.1 (User Only)	Administrator	FMT_MOF_EXT.1.2 (Admin Only)
<p>25. <i>list of protocols where the device acts as a server</i> = Protocols supporting wireless remote access. This function is not mandated if there is no native MD support for wireless remote access. Mobile hotspot connections (see function 41) are not considered wireless remote access if the wireless device connected to the MD cannot access the application processor.</p> <p>32. It is acceptable for the audit logs to be read remotely by the MDM.</p> <p>37. Auditable event in Table 1:</p> <ul style="list-style-type: none"> FPT_TST_EXT.2, Detected integrity violation <p>Auditable events in Table 2:</p> <ul style="list-style-type: none"> FIA_UAU.6 User changes Password Authentication Factor FPT_TUD_EXT.2 Success or failure of signature verification for software updates FPT_TUD_EXT.3 Success or failure of signature verification for applications <p>40. Remote systems include cloud-based systems.</p> <p>41. If MD supports hotspot feature, selection <i>pre-shared key</i> must be included by the ST author. If MD supports USB tethering, either selections <i>pre-shared key</i> or <i>passcode</i> may be included by the ST author. For hotspot functionality, pre-shared keys derived from passcodes are acceptable; simple password authentication is not. If the TOE forces use of a single compliant sub-selection for a or b (i.e., it does not allow configuration of this parameter), then the ST author does not need to specify management functionality for that feature.</p> <p>42. Data or application sharing between different application processes or groups of application processes (including copy/paste of data) are considered an exception to the access control policy and therefore, the Administrator must be able to enable/disable these features.</p> <p>44. An acceptable alternative to restricting a user's ability to unenroll an MD in management is for the MD to automatically perform a wipe of protected data upon unenrollment.</p>				

Table 3-3: Management Functions (From PP-Module for Bluetooth)

Management Function	FMT_SMF_EXT.1	FMT_MOF_EXT.1.1 (User Only)	Administrator	FMT_MOF_EXT.1.2 (Admin Only)
<div> Status Markers: M – Mandatory O – Optional/Objective Red highlighted text – Deviations from PP-Module </div>				
FMT_SMF_EXT.1.1/BLUETOOTH BT-8 Disable/enable the Bluetooth [<i>assignment: all profiles supported by the OS</i>]	M	-	M	M

Table 3-4: Management Functions (From MDFPP Extended Package for WLAN Clients)

Management Function	FMT_SMF_EXT.1	FMT_MOF_EXT.1.1 (User Only)	Administrator	FMT_MOF_EXT.1.2 (Admin Only)
<div> Status Markers: M – Mandatory O – Optional/Objective Red highlighted text – Deviations from Extended Package for WLAN Clients </div>				
FMT_SMF_EXT.1.1/WLAN				
<ul style="list-style-type: none"> disable ad hoc wireless client-to-client connection capability disable wireless network bridging capability 	M M	- -	M M	M M

3.2 DoD-Mandated Selection-Based, Optional, and Objective Functions

The following Security Functional Requirements (and associated selections and assignments) listed as objective in the PP are mandated for the DoD:

- FAU_SAR.1.1
- FAU_SAR.1.2
- FIA_UAU_EXT.4.1
- FIA_UAU_EXT.4.2
- FPT_BBD_EXT.1.1

- FPT_TUD_EXT.5.1 Application note: If the requirement is not supported by an operating system, appropriate mitigations should be provided.
- FPT_TUD_EXT.6.1
- FTA_TAB.1.1

4. OTHER DOD MANDATES

4.1 Federal Information Processing Standard (FIPS) 140-2

Cryptographic modules supporting any SFR in the Cryptographic Support (FCS) class must be FIPS140-2 validated. Information concerning FIPS 140-2 validation should be included in the ST. Failure to obtain validation to include applications could preclude use of the TOE within DoD.

4.2 Federal Information Processing Standard (FIPS) 201-2

The TOE is expected to interface with FIPS 201-2 compliant credentials (including derived credentials as described in NIST SP 800-157). The TOE may connect to a peripheral device (e.g., a smart card reader) to interface with PIV credentials or natively store derived credentials (whose protections are evaluated in the Protection Profile).

4.3 Core and Carrier-Installed Applications on Mobile Devices

Core and vendor-installed applications are expected to go through an authorized DoD mobile application vetting process to identify the risk of their use and compensating controls. These applications are subject to the application installation policy of Function 8b in FMF_MOF_EXT.1.2 and FMF_SMF_EXT.1.1 regardless of the fact that they were not installed by the device user.

4.4 DoD-Mandated Configuration

The table below lists configuration values for product features implementing the PP Specification of Management Functions (FMT_SMF). The ST is not expected to include this configuration information, but it will be included in the product-specific STIG associated with the evaluated IT product.

Table 4-1: Configuration Values

FMT_SMF_EXT.1 Function	DoD Selections and Values
Function 1	<p>minimum password length = 6 characters minimum password complexity = <i>the password must not contain more than four sequential or repeating characters</i> (e.g., the sequences 11111, 23456, 76543, nnnnn, vwxyz, edcba placed anywhere within the password would violate the complexity rule). No maximum password lifetime is required.</p> <p>Application note: The MDF PP does not provide selections for password complexity. Therefore, the DoD-mandated complexity rule described above is not included in the MDF PP. Vendors must either provide the capability to support this rule or justify why an alternative supported complexity scheme offers</p>

FMT_SMF_EXT.1 Function	DoD Selections and Values
	equivalent or stronger protection against the vulnerability of easily guessed or simple passwords.
Function 2	screen lock <i>enabled</i> screen lock timeout = <i>15 minutes or less</i> number of authentication failures = <i>10 or fewer</i>
Function 8	Sources of applications = <i>list of DoD-approved commercial app repository, MDM server, or mobile application store</i> Application whitelist <i>application characteristics</i> = <i>list of digital signatures, cryptographic hash values, or names and versions</i> Applications with the following characteristics may not be placed on the application whitelist: - <i>backup MD data to non-DoD cloud servers (including user and application access to cloud backup services),</i> - <i>transmit MD diagnostic data to non-DoD servers,</i> - <i>voice assistant application if available when MD is locked,</i> - <i>voice dialing application if available when MD is locked,</i> - <i>allows synchronization of data or applications between devices associated with user,</i> - <i>allows unencrypted (or encrypted but not FIPS 140-2 validated) data sharing with other MDs or printers.</i>
Function 18	<i>Disable</i> all notifications (unless implementation follows per app approach discussed in Application note for Function 18 in Table 3-2)
Function 19	<i>Enable</i>
Function 20	<i>Enable (or disable removable media use if encryption is not available)</i>
Function 22	<i>Enable</i> for biometric technologies validated by NIAP and approved by Authorizing Official (AO).
Function 25	<i>Disable protocols supporting wireless remote access.</i> Application note: A mobile device providing personal hotspot functionality is not considered supporting wireless remote access if the functionality only provides access to a distribution network (such as a mobile carrier's cellular data network) and does not provide access to the application processor.
Function 26	<i>Disable</i>
Function 27	<i>Disable</i>
Function 33	certificate = <i>DoD-approved certificate(s)</i> , public key = <i>DoD-approved public key(s)</i> Application note: To the extent this parameter is configurable, it must be populated with DoD-approved

FMT_SMF_EXT.1 Function	DoD Selections and Values
	certificates or public keys. There is no requirement that it be configurable; such certificates or public keys may be pre-populated with the operating system software.
Function 36	<p>If required banner text is not included in the signed User Agreement and mobile device operating system has the capability to configure the banner:</p> <p>Configure: For devices accommodating advisory warning messages of 1300 characters: <i>You are accessing a U.S. Government (USG) Information System (IS) that is provided for USG-authorized use only.</i> <i>By using this IS (which includes any device attached to this IS), you consent to the following conditions:</i> -<i>The USG routinely intercepts and monitors communications on this IS for purposes including, but not limited to, penetration testing, COMSEC monitoring, network operations and defense, personnel misconduct (PM), law enforcement (LE), and counterintelligence (CI) investigations.</i> -<i>At any time, the USG may inspect and seize data stored on this IS.</i> -<i>Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed or used for any USG-authorized purpose.</i> -<i>Communications using, or data stored on, this IS are not private, are subject to routine monitoring, interception, and search, and may be disclosed or used for any USG-authorized purpose.</i> -<i>This IS includes security measures (e.g., authentication and access controls) to protect USG interests--not for your personal benefit or privacy.</i> -<i>Notwithstanding the above, using this IS does not constitute consent to PM, LE or CI investigative searching or monitoring of the content of privileged communications, or work product, related to personal representation or services by attorneys, psychotherapists, or clergy, and their assistants. Such communications and work product are private and confidential. See User Agreement for details.</i></p> <p>For mobile devices with severe character limitations: <i>I've read & consent to terms in IS user agreem't.</i></p>

FMT_SMF_EXT.1 Function	DoD Selections and Values
	Application note: To the extent permitted by the operating system, the system should be configured to prevent further activity on the information system unless and until the user executes a positive action to manifest agreement to the advisory message. An image with the required banner text is an acceptable method for implementing this requirement.
Function 37	Configure: Auditable event in Table 1: <ul style="list-style-type: none"> FPT_TST_EXT.2, Detected integrity violation Application note: Requirement applies only to integrity violation detections that can be logged by the audit logging component. Auditable events in Table 2: <ul style="list-style-type: none"> FIA_UAU.6 FPT_TUD_EXT.2 Success or failure of signature verification for applications FPT_TUD_EXT.3 Success or failure of signature verification for applications
Function 39	Disable USB mass storage mode
Function 40	Disable backup to locally connected system Disable backup to remote system
Function 41	Enable Hotspot functionality authenticated by <i>preshared key</i> Enable USB tethering authentication Application note: If hotspot functionality permitted, it must be authenticated via preshared key. If USB tethering is permitted, the connection must be authenticated. There is no requirement to enable hotspot functionality or USB tethering.
Function 42	Disable
Function 47	Disable multi-user modes (if feature supported by MD)
FMT_SMF_EXT.2.1 Function	Enable [selection: wipe protected data, wipe sensitive data] upon unenrollment from MDM Enable [selection: remove Enterprise applications, remove all non-core applications (any non-factory installed application) upon unenrollment from MDM
FMT_SMF_EXT.1.1/BLUETOOTH BT-8	Disable all Bluetooth profiles except for HSP (Headset Profile), HFP (HandsFree Profile), SPP (Serial Port Profile), A2DP (Advanced Audio Distribution Profile), AVRCP (Audio/Video Remote Control Profile), and PBAP (Phone Book Access Profile)
FMT_SMF_EXT.1.1/WLAN	Disable ad hoc wireless client-to-client connection capability